SAFETY DATA SHEET



Revision Date 08-May-2018

Version 6.01

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Rocket Red™ Paint

Product code 215-13

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Paint

Restrictions on use No information available

1.3 Details of the supplier of the safety data sheet

Supplier DayGlo Color Corp.

4515 St. Clair Avenue Cleveland, OH 44103 (216) 391-7070

+1 216-391-7070 (outside the US)

E-mail Address ehs@dayglo.com

1.4 Emergency telephone number

Emergency telephone number Chemtrec: +1 703-527-3887 ex-USA

Chemtrec: 1-800-424-9300 USA

2. Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

Aspiration toxicity	Category 1
Flammable liquids	Category 3

2.2 Label elements

Signal Word

Danger

Hazard Statements

May be fatal if swallowed and enters airways

Flammable liquid and vapor



Precautionary Statements - Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/Bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge Wear protective gloves/clothing and eye/face protection

Precautionary Statements - Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

2.4 Other information

Not Applicable

Unknown Acute Toxicity

35.08829328% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/Information on Ingredients

Substance Mixture

Chemical Name	CAS No.	Weight-%
Distillates, petroleum, hydrotreated light	64742-47-8	30 - 40
C.I. Basic Red 1:1	3068-39-1	< 1
Stoddard Solvent	8052-41-3	< 1
Methyl ethyl ketoxime	96-29-7	< 0.1

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

4.1 Description of first-aid measures

General advice Show this safety data sheet to the doctor in attendance. When symptoms persist or in all

cases of doubt seek medical advice.

Eye contact Remove contact lenses, if present. Rinse immediately with plenty of water, also under the

Transor contact of loos, it process. Transo in modulatory was plotted and a large

eyelids, for at least 15 minutes. Call a physician if irritation develops or persists.

Skin contact Wash off immediately with soap and plenty of water. Remove all contaminated clothes and

shoes. If skin irritation persists, call a physician.

Inhalation Consult a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms See Section 2.2, Label Elements and/or Section 11, Toxicological effects.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. Fire-Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, fog, Carbon dioxide (CO2), foam or dry chemical.

Unsuitable Extinguishing Media High volume water jet.

5.2 Special hazards arising from the substance or mixture

Special Hazard

Hazardous decomposition products formed under fire conditions. Immediately place absorbent material in a sealed water-filled metal container to avoid spontaneous combustion of absorbent material contaminated with this product.

Hazardous Combustion Products No information available.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

5.3 Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. See Section 12 for additional Ecological information.

6.3 Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material. Prevent product from entering drains. Ground and

bond containers when transferring material. Keep in suitable and closed containers for

disposal.

7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take necessary

action to avoid static electricity discharge (which might cause ignition of organic vapors).

Hygiene measures When using, do not eat, drink or smoke. Wash hands before breaks and at the end of

workday. Remove and wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat and sources of ignition. Keep container tightly closed in a dry and

well-ventilated place.

Materials to Avoid Strong oxidizing agents.

8. Exposure controls/personal protection

8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Distillates, petroleum,	-	-	TWA: 200 mg/m ³			
hydrotreated light			Skin			
64742-47-8						
Stoddard Solvent	TWA: 100 ppm	TWA: 500 ppm	TWA: 290 mg/m ³	TWA: 100 ppm	TWA: 100 ppm	TWA: 525 mg/m ³
8052-41-3		TWA: 2900 mg/m ³	STEL: 580 mg/m ³	TWA: 572 mg/m ³	TWA: 525 mg/m ³	_

8.2 Appropriate engineering controls

Engineering Measures Ensure adequate ventilation, especially in confined areas.

8.3 Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear chemical-resistant glasses and/or goggles and a face shield when eye and face

contact is possible due to handling and processing of material.

Skin and body protection Long sleeved clothing.

Respiratory protection Respirator with filter for organic vapor. If these are not sufficient to maintain concentrations

of particulates and solvent vapor below the OEL, suitable respiratory protection must be

worn.

Hygiene measures See section 7 for more information

Revision Date 08-May-2018 215-13 - Rocket Red™ Paint

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Liquid

Appearance Liquid Color Red

Odor Threshold No information available Odor Solvent

Property Values Remarks • Methods

No information available pН

No information available

Melting/freezing point

Boiling point/boiling range 154 °C / 309 °F Flash Point 41 °C / 106 °F

Evaporation rate No information available no data available

No information available Flammability (solid, gas)

Flammability Limits in Air upper flammability limit No information available

lower flammability limit No information available Vapor pressure No information available

Vapor density No information available

Specific Gravity 1.05

Water solubility Insoluble in water

Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Viscosity, kinematic No information available Viscosity, dynamic No information available

Explosive properties No information available **Oxidizing Properties** No information available

9.2 Other information

Volatile organic compounds (VOC) 383 g/L

content

10. Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

None under normal processing.

10.4 Conditions to Avoid

Heat, flames and sparks.

10.5 Incompatible Materials

Strong oxidizing agents.

10.6 Hazardous Decomposition Products

Carbon oxides. Nitrogen oxides (NOx).

11. Toxicological information

11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity 35.08829328% of the mixture consists of ingredient(s) of unknown toxicity

 Oral LD50
 14,266.00 mg/kg

 Dermal LD50
 5,706.00 mg/kg

 LC50 (Dust/Mist)
 6.31 mg/l

Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates, petroleum, hydrotreated light 64742-47-8	5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h
C.I. Basic Red 1:1 3068-39-1	449 mg/kg (Rat)	2,500 mg/kg (Rat)	0.05 mg/l (4 hour)
Methyl ethyl ketoxime 96-29-7	930 mg/kg (Rat)	> 1000 mg/kg (Rabbit), 24-hr	= 20 mg/L (Rat) 4 h

11.2 Information on toxicological effects

Skin corrosion/irritation

Product Information

Irritating to skin

Component Information

• No information available

Serious eye damage/eye irritation

Product Information

· Irritating to eyes

Component Information

No information available

Respiratory or skin sensitization

Product Information

· May be harmful if inhaled

Component Information

• No information available

Germ cell mutagenicity

Product Information

· No information available

Component Information

· No information available

Carcinogenicity

Product Information

• This product contains <0.1% free formaldehyde and may be capable of outgassing formaldehyde at levels in excess of OSHA's Action Level under some conditions of use. Formaldehyde is a known cancer hazard. Long term exposure may result in dermatitis or respiratory sensitization for sensitive individuals.

Component Information

No information available

Reproductive toxicity

Product Information

No information available

Component Information

• No information available

STOT - single exposure

No information available

STOT - repeated exposure

No information available

Other adverse effects

Product Information

- No information available
- Component Information
- No information available

Aspiration hazard

Product Information

- · No information available
- **Component Information**
- · No information available

12. Ecological information

12.1 Toxicity

Ecotoxicity

No information available

< 1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Ecotoxicity effects

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Distillates, petroleum, hydrotreated light 64742-47-8	-	LC50: 96 h Pimephales promelas 45 mg/L flow-through LC50: 96 h Lepomis macrochirus 2.2 mg/L static LC50: 96 h Oncorhynchus mykiss 2.4 mg/L static	-
Methyl ethyl ketoxime 96-29-7	EC50: 72 h Desmodesmus subspicatus 83 mg/L	LC50: 96 h Pimephales promelas 777 - 914 mg/L flow-through LC50: 96 h Poecilia reticulata 760 mg/L static	EC50: 48 h Daphnia magna 750 mg/L

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
Methyl ethyl ketoxime 96-29-7	0.65

12.4 Mobility in soil

No information available.

12.5 Other adverse effects

Discharge into the environment must be avoided

13. Disposal Considerations

13.1 Waste treatment methods

Dispose of in accordance with local regulations.

14. Transport Information

DOT Not regulated (If shipped in NON BULK packaging by ground transport)

MEX no data available

IMDG

Proper shipping name UN1263, Paint, 3, PGIII

Hazard class 3 UN UN1263 Packing Group PGIII

IATA

UN UN1263

Proper shipping name UN1263, Paint, 3, PGIII

Proper shipping name Flammable Liquid, n.o.s. (Mineral Spirits)

Hazard class 3
Packing Group PGIII

15. Regulatory information

15.1 International Inventories

TSCA Complies Complies

EINECS/ELINCS ENCS IECSC KECL PICCS AICS NZIOC -

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

15.2 U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

15.3 Pesticide Information

Not applicable

15.4 U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Formaldehyde - 50-00-0	Carcinogen
C.I. Basic Violet 10 - 81-88-9	Carcinogen

16. Other information

NFPA Health Hazard - Flammability - Instability - Physical and chemical

hazards -

HMIS Health Hazard 2 Flammability 2 Physical Hazard 0 Personal protection X

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

Ceiling (C)

DOT (Department of Transportation)

EPA (Environmental Protection Agency)

IARC (International Agency for Research on Cancer)

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG)

NIOSH (National Institute for Occupational Safety and Health)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEL (Permissible Exposure Limit)

Reportable Quantity (RQ)

Skin designation (S*)

STEL (Short Term Exposure Limit)

TLV® (Threshold Limit Value)

TWA (time-weighted average)

Prepared By No information available DayGlo Color Corp.

Regulatory Affairs/Product Safety

Revision Date 08-May-2018

Revision Note

No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet