

Technical Data Sheet

Endure[™] Hi-Vis Brushing Paint

General description

From the inventors of fluorescent color, DayGlo Endure Hi-Vis Brushing Paint is an extremely bright and fade resistant alkyd fluorescent paint for interior and exterior use.

Uniquely bright, Endure Hi-Vis Brushing Paint has a strong fluorescent response. Designed to withstand harsh environmental conditions and maintain brightness and effectiveness, perfect for hi-vis safety applications. More fade-resistant than traditional fluorescent paint, Endure Hi-Vis is versatile and can be used on multiple substrates; anywhere that requires the end product to be seen.

For a higher gloss finish use DayGlo Filteray[®] D Clear Overcoat. (DayGlo Filteray[®] D maximizes lightfastness and film integrity.) DayGlo Filteray[®] D

Overcoat is not recommended for use where exposed

Available Colors	
Product Code	Color
215-34	Safety Yellow
215-08A	Filteray [®] D Clear Overcoat
Packaging:	
1 Quart Cans 1 Gallon Cans	

Storage & shelf life:

24 months when kept in closed original packaging in a dry place at ambient temperature.

Safety & regulatory:

Safety Data Sheet available on request.

to black light – fluorescent surfaces coated with DayGlo Filteray[®] D will not fluoresce in the dark under black light).

Filteray Type D is a clear overcoat designed for use over the Endure Hi-Vis brushing paint. It absorbs some of the sun's harmful rays that cause premature fading of fluorescent colors during continued exposure to direct sunlight.

The final surface produced by the Filteray Type D overcoat is harder and has a higher gloss than the DayGlo Endure Hi-Vis Brushing Paint alone. This makes it more resistant to wear and easier to clean. The quantity of Filteray Type D overcoat required is usually 2/3 that of the paint.

Applications

The DayGlo Endure Hi-Vis Brushing Paint can be used anywhere that requires a high visibility brushing paint. Some of the general areas of use include:

Graphic arts:

- For outdoor advertising signs
- Painted bulletins

- Truck signs
- Trade exhibits

• Store signs

Disclaimer: Our technical advice, information, statements, whether given verbally, in writing, or in the form of test results, is offered for your guidance without warranty. No warranty for fitness for a particular purpose is made. This also applies where protective rights of third parties are involved. It does not release the user from obligation to test the suitability of the products and formulas for the intended process and applications. Our guarantee is limited to the consistent quality of our product.



Safety:

- Aviation
- industrial and marine uses on aircraft
- ground support equipment
- navigational aids
- safety markings, equipment
- machinery
- fire protection equipment

- First aid kits
- Traffic controls
- Boats
- Buoys
- Docks
- Life saving equipment

Hobby/sports:

- Models and toys
- Markings on easily lost sporting equipment (boomerangs, arrows, fishing gear)
- Identification markings on personal equipment

Physical properties	
Delivery form	Liquid paint
Hegman grind	5.0 Min
Viscosity	1,500-2,000 cps @ 77*F