

Safety Data Sheet

1. Identification

Product Information. 215-46

Product Name: Lightning Yellow Paint

Recommended Use. Paint

Uses advised against. No information available

Supplier. DayGlo Color Corp.

4515 St. Clair Avenue Cleveland, OH 44102 (216) 391-7070

+1 216-391-7070 (outside the US)

Emergency telephone number. Chemtrec: +1-800-424-9300 USA

Chemtrec: +1 703-527-3887 ex-USA

24 hrs./day, 7 days/week

2. Hazards Identification

GHS Classification in accordance with 29 CFR 1910.1200

Carcinogenicity, category 1B Flammable Liquid, category 3 Reproductive Toxicity, category 1B Skin Sensitizer, category 1 Aspiration Hazard, category 1

GHS Pictograms







Signal Word

Danger

Unknown Acute Toxicity

< 0.1% of the mixture consists of ingredient(s) of unknown acute toxicity

HAZARD STATEMENTS

Flammable liquid and vapor.

May be fatal if swallowed and enters airways.

May cause an allergic skin reaction.

May cause cancer.

May damage fertility or the unborn child.

Precautionary Statements - Prevention.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, sparks, open flames, hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Product name.: 215-46 Lightning Yellow Paint

Wear protective gloves, protective clothing, eye protection, face protection

Precautionary Statements - Response.

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

In case of fire: Use CO₂ dry chemical or foam to extinguish.

Precautionary Statements - Storage.

Store in a well-ventilated place. Keep cool.

Store locked up.

Precautionary Statements - Disposal.

Dispose of contents in accordance with local, regional, national, international regulations.

3. Composition/Information on Ingredients

| Chemical Name | CAS-No. | <u>Wt. %</u> |
|--|------------|--------------|
| Distillates, petroleum, hydrotreated light | 64742-47-8 | 25-50 |
| XYLENE | 1330-20-7 | 0.1-1.0 |
| Naphtha, Petroleum Hydrotreated Heavy | 64742-48-9 | 0.1-1.0 |
| Methyl ethyl ketoxime | 96-29-7 | 0.1-1.0 |
| Ethyl Benzene | 100-41-4 | 0.1-1.0 |
| ZIRCONIUM 2-ETHYLHEXANOATE | 22464-99-9 | 0.1-1.0 |

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid Measures

Description of first-aid measures.

General advice.

No Information

Inhalation.

Consult a physician.

Skin contact.

If skin irritation persists, call a physician.

Eye contact.

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Ingestion.

Do NOT induce vomiting. Drink plenty of water. Call a physician immediately.

Symptoms.

See Section 2 and Section 11, Toxicological effects for description of potential symptoms.

Notes to physician.

Treat symptomatically.

5. Fire-fighting Measures

Extinguishing media.

Suitable extinguishing media.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Extinguishing media which shall not be used for safety reasons.

None.

Special hazards arising from the substance or mixture.

Flammable. In the event of fire and/or explosion do not breathe fumes.

Advice for firefighters.

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures.

Personal precautions.

Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Ensure adequate ventilation, especially in confined areas.

Advice for emergency responders.

No Information

Environmental precautions.

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological information.

Methods and materials for containment and cleaning up.

Methods for Containment.

Soak up with inert absorbent material. Prevent product from entering drains. Keep in suitable and closed containers for disposal.

Methods for cleaning up.

No Information

Reference to other sections.

See section 8 for more information.

7. Handling and Storage

Conditions for safe storage, including any incompatibilities.

Advice on safe handling.

Keep away from heat, sparks and open flame. No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Hygiene measures.

Handle in accordance with good industrial hygiene and safety practice.

Storage Conditions.

Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place. Keep away from heat and sources of ignition.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

| Chemical Name | ACGIH TLV-TWA | ACGIH-TLV STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|---------------|---------------|----------------|--------------|------------------|
| XYLENE | 20 ppm | N.E. | 100 ppm | N.E. |
| Ethyl Benzene | 20 ppm | N.E. | 100 ppm | N.E. |

TLV = Threshold Limit Value TWA = Time Weighted Average PEL = Permissible Exposure Limit STEL = Short-Term Exposure Limit N.E. = Not Established

Engineering Measures.

Showers, eyewash stations, and ventilation systems.

Personal protective equipment.

Eye/Face Protection.

Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to handling and processing of material.

Skin and body protection.

No Information

Respiratory protection.

No Information

9. Physical and chemical properties.

Information on basic physical and chemical properties.

Physical state Liquid

Appearance No Information Yellow

Odor Solvent

Odor Threshold

PH

No Information

Evaporation rate No Information Available

Explosive properties.No InformationVapor pressure.No InformationVapor density.No Information

Specific Gravity. (g/cm³) 1.050

Water solubility.Insoluble in waterPartition coefficient.No InformationAutoignition temperature.,°CNo InformationDecomposition Temperature °C.No InformationViscosity, kinematic.No Information

Other information.

Volatile organic compounds (VOC) content. 383 g/L

Density, lb/gal No Information

10. Stability and Reactivity

Reactivity.

No dangerous reaction known under conditions of normal use.

Chemical stability.

Stable. Heat, flames and sparks.

Possibility of hazardous reactions.

Hazardous polymerization does not occur.

Conditions to Avoid.

None known.

Incompatible Materials.

None under normal processing.

Hazardous Decomposition Products.

Carbon oxides. Nitrogen oxides (NO_x).

11. Toxicological Information

Information on toxicological effects.

Acute toxicity.

Product Information

No Information

Component Information.

| CAS-No. | Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|------------|---------------------------------------|----------------|------------------------------|------------------------|
| 1330-20-7 | XYLENE | 3500 mg/kg Rat | >4350 mg/kg Rabbit | 29.08 mg/L Rat (Vapor) |
| 64742-48-9 | Naphtha, Petroleum Hydrotreated Heavy | N.I. | N.I. | > 4.98 Rat (Dust) |
| 96-29-7 | Methyl ethyl ketoxime | 930 mg/kg Rat | 1000 - 1800 mg/ kg Rabbit | >4.83 mg/L Rat (Vapor) |
| 100-41-4 | Ethyl Benzene | 3500 mg/kg Rat | 15400 mg/kg Rabbit | NA (Dust) |

N.I. = No Information

Skin corrosion/irritation.

Irritating to skin. SKIN IRRITANT.

Eye damage/irritation.

Irritating to eyes.

Respiratory or skin sensitization.

May cause drownsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists. May cause allergic skin reaction.

Ingestion.

No Information

Germ cell mutagenicity.

No Information

Carcinogenicity.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

| CAS-No. | Chemical Name | <u>IARC</u> | <u>NTP</u> | <u>OSHA</u> |
|-----------|---------------|---------------|------------|-------------|
| 1330-20-7 | XYLENE | IARC Group 3 | - | - |
| 100-41-4 | Ethyl Benzene | IARC Group 2B | - | - |

Reproductive toxicity.

May damage fertility or the unborn child.

Specific target organ systemic toxicity (single exposure).

No Information

Specific target organ systemic toxicity (repeated exposure).

No Information

Aspiration hazard.

No Information

Primary Route(s) of Entry

No Information

12. Ecological Information

Toxicity.

0.11% of the mixture consists of ingredient(s) of unknown aquatic toxicity

Ecotoxicity effects.

| Chemical Name | Toxicity to algae | | Toxicity to daphnia and other aquatic invertebrates |
|---|-------------------|--|---|
| Distillates, petroleum, hydrotreated light 64742-47-8 | - | LC50 96 h Pimephales promelas 45 mg/L, LC50 96 h Lepomis macrochirus 2.2 mg/L, LC50 96 h Oncorhynchus mykiss 2.4 mg/L | _ |

| XYLENE 1330-20-7 | - | LC50 96 h Pimephales promelas 13.4 mg/L, LC50 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L, LC50 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L, LC50 96 h Lepomis macrochirus 13.1 - 16.5 mg/L, LC50 96 h Lepomis macrochirus 19 mg/L, LC50 96 h Lepomis macrochirus 7.711 - 9.591 mg/L, LC50 96 h Pimephales promelas 23.53 - 29.97 mg/L, LC50 96 h Cyprinus carpio 780 mg/L, LC50 96 h Cyprinus carpio >780 mg/L, LC50 96 h Poecilia reticulata 30.26 - 40. | EC50 48 h water flea 3.82 mg/L, LC50 48 h Gammarus lacustris 0.6 mg/L |
|--|---|--|---|
| Naphtha, Petroleum Hydrotreated Heavy 64742-48-9 | - | LC50 96 h Rainbow trout, donaldson trout 8.8 mg/L | - |
| Methyl ethyl ketoxime 96-29-7 | EC50 72 h Desmodesmus subspicatus 83 mg/L | LC50 96 h Pimephales promelas 777 - 914 mg/L, LC50 96 h Poecilia reticulata 760 mg/L | EC50 48 h Daphnia magna 750 mg/L |
| Ethyl Benzene 100-41-4 | EC50 72 h Pseudokirchneriella subcapitata 4.6 mg/L, EC50 96 h Pseudokirchneriella subcapitata >438 mg/L, EC50 72 h Pseudokirchneriella subcapitata 2.6 - 11.3 mg/L, EC50 96 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L | LC50 96 h Oncorhynchus mykiss 11.0 - 18.0 mg/L, LC50 96 h Oncorhynchus mykiss 4.2 mg/L, LC50 96 h Pimephales promelas 7.55 - 11 mg/L, LC50 96 h Lepomis macrochirus 32 mg/L, LC50 96 h Pimephales promelas 9.1 - 15.6 mg/L, LC50 96 h Poecilia reticulata 9.6 mg/L | EC50 48 h Daphnia magna 1.8 - 2.4 mg/L |

Persistence and degradability.

No data are available on the product itself.

Bioaccumulative potential.

Discharge into the environment must be avoided.

| CAS-No. | Chemical Name | log POW |
|-----------|-----------------------|-------------|
| 1330-20-7 | XYLENE | 2.77 - 3.15 |
| 96-29-7 | Methyl ethyl ketoxime | 0.65 |
| 100-41-4 | Ethyl Benzene | 3.6 |

Mobility in soil.

No information

Other adverse effects.

No information

13. Disposal Considerations

Waste Disposal Guidance.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. Transport Information

<u>DOT</u>

Shipping Name: Not regulated. (If shipped in NON BULK packaging by ground transport)

UN/NA Number: UN1263
Packing Group: III

<u>IMDG</u>

Proper Shipping Name: UN1263, Paint, 3, PGIII

Hazard Class: 3 UN Number: UN1263 Packing Group: PGIII

Product name.: 215-46 Lightning Yellow Paint

IATA

Proper Shipping Name: UN1263, Paint, 3, PGIII

Hazard Class: 3

UN Number: UN1263 Packing Group: PGIII

15. Regulatory Information

International Inventories:

TSCA Complies
DSL Complies

DSL/NDSL EINECS/ELINCS ENCS IECSC KECI PICCS AIIC NZIOC -

TCSI

TSCA United States Toxic Substances Control Act Section 8(b) Inventory.

DSL Canadian Domestic Substances List.

DSL/NDSL Canadian Domestic Substances List/Canadian Non-Domestic Substances List

EINECS/ELINCS European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.

ENCS Japan Existing and New Chemical Substances.
 IECSC China Inventory of Existing Chemical Substances.
 KECL Korean Existing and Evaluated Chemical Substances.
 Place Place Philippines Inventory of Chemicals and Chemical Substances.

AllC Australian Inventory of Chemical Substances.

NZIOC New Zealand Inventory of Chemicals.

TCSI Taiwan Chemical Substance Inventory

U.S. Federal Regulations:

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372: .

<u>Chemical Name</u> <u>CAS-No.</u> <u>Weight Percent</u>

Ethyl Benzene 100-41-4 0.1-1.0

TOXIC SUBSTANCES CONTROL ACT 12(b):

This product does not contain any chemicals that are subject to the reporting requirements of TSCA 12(b).

ADDITIONAL INFORMATION

Additional Information - Sxn 15: No Information

CALIFORNIA PROPOSITION 65 CARCINOGENS



WARNING

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

 Chemical Name
 CAS-No.

 Ethyl Benzene
 100-41-4

 Formaldehyde
 50-00-0

 C.I. Basic Violet 10
 81-88-9

Product name.: 215-46 Lightning Yellow Paint

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

No Proposition 65 Reproductive Toxins exist in this product.

16. Other Information

Revision Date: 4/1/2024 Supersedes Date: 4/1/2024

Reason for revision: No Information

Datasheet produced by: Regulatory Department

HMIS Ratings:

| Health: 2* Flammability: 2 Physical Hazard: 0 Personal Protection: | X |
|--|---|
|--|---|

NFPA Ratings:

| | | • | | | | | | |
|---|---------|------|---------------|------|--------------|------|----------------------|------|
| Ī | Health: | N.I. | Flammability: | N.I. | Instability: | N.I. | Physical & Chemical: | N.I. |

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.