

# Technical Data Sheet

## SCREAMIN' (SRX) Paint

### General description

DayGlo® SRX latex paint is a premium fluorescent, water-based paint. To ensure maximum lightfastness and film integrity, use together with DayGlo Filteray® Type W.

Studies indicate that if a single color is desired for impact, Blaze Orange is generally best for contrast with natural backgrounds. DayGlo's fluorescent colors do not tend to appear white, gray, or black (achromatic) at extreme distances or low light conditions as non-fluorescent colors do. This is ideal for signage and any product requires high visibility.

Filteray Type W is a clear overcoat designed for use over the SRX latex paint. It absorbs some of the sun's harmful rays that cause premature fading of fluorescent colors during continued exposure to direct sunlight.

A top coat of Filteray Type W improves the lightfastness of DayGlo fluorescent colors. Ordinary varnishes and overcoats lack the protective action of Filteray Type W overcoat and can do more harm than good when used over DayGlo fluorescent colors.

The final surface produced by the Filteray W overcoat is harder and has a higher gloss than the DayGlo SRX latex paint alone. This makes it more resistant to wear and easier to clean. The quantity of Filteray Type D overcoat required is usually 2/3 that of the paint.

### Applications

The DayGlo SRX latex paint can be used anywhere that requires a high visibility brushing paint. Some of the general areas of use include:

Theatrical and Special Effects:

- For use in haunted houses and stage painting
- They can also be used to create 3-D image

Graphic Arts:

Disclaimer: Our technical advice, information, statements, whether given verbally, in writing, or in the form of test results, is offered for your guidance without warranty. No warranty for fitness for a particular purpose is made. This also applies where protective rights of third parties are involved. It does not release the user from obligation to test the suitability of the products and formulas for the intended process and applications. Our guarantee is limited to the consistent quality of our product.

Rev 1.00\_2023.02.16 5/19/2023

### Available Colors

Product Code	Color
SRX-11	Aurora Pink
SRX-13	Rocket Red
SRX-15	Blaze Orange
SRX-17	Saturn Yellow
SRX-18	Signal Green
SRX-19	Horizon Blue
SRX-20	Ultra Violet
SRX-08A	Filteray® W Top Coat

### Packaging:

1 Quart Cans  
1 Gallon Cans

### Storage & shelf life:

12 months when kept in closed original packaging in a dry place at ambient temperature.

### Safety & regulatory:

Safety Data Sheet available on request.

- For outdoor advertising signs
- Murals
- Painted bulletins
- Store signs
- Truck signs
- Trade exhibits

**Safety:**

- Aviation
- industrial and marine uses on aircraft
- ground support equipment
- navigational aids
- safety markings
- equipment
- machinery
- fire protection equipment
- first aid kits
- traffic controls
- boats
- buoys
- docks
- life-saving equipment

**Hobby-Sports:**

- Models and toys
- Markings on easily lost sporting equipment (boomerangs, arrows, fishing gear)
- Identification markings on personal equipment

**Features**

- Formaldehyde Free Formulation
- Low Odor
- Environmentally Friendly
- 100% Acrylic Latex

Physical properties	
Delivery form	Liquid paint
Hegman grind	5.0 Min
Viscosity	1,500 - 2,500 cps @ 77°F
pH	8.00-9.00

**Lightfastness**

The useful outdoor life of the color is determined by the thickness and uniformity of the DayGlo SRX coating. To greatly increase resistance to sunlight, apply an overcoat of Filteray Type D.

One coat of DayGlo SRX latex paint is usually sufficient for interior markings, as the color is virtually unaffected by light sources other than direct sunlight. For storefronts, panel truck signs, etc., which must last a year or more, apply a coat of Filteray W overcoat over two coats of DayGlo SRX latex paint.

Disclaimer: Our technical advice, information, statements, whether given verbally, in writing, or in the form of test results, is offered for your guidance without warranty. No warranty for fitness for a particular purpose is made. This also applies where protective rights of third parties are involved. It does not release the user from obligation to test the suitability of the products and formulas for the intended process and applications. Our guarantee is limited to the consistent quality of our product.